

ERGO-SHARK Right-Hand Laser Mouse M-100R



Facts & Features

- Optimal precision thanks to built-in switch for simple resolution switch between 800 dpi and 1600 dpi
- Exact and rapid positioning of the cursor thanks to the latest laser scanning
- High-end Teflon sliding surfaces for easy movement of the mouse
- Soft-touch surface for pleasant handling
- Designed for right-handed use
Adapted to suit the requirements of right-handed use
- 4-way scroll function
- 7 buttons, all freely programmable thanks to easy-to-use KeyM@n-Software
- Quick and rapid data transfer
- 1.8 m cable with USB connection, incl. PS/2 adapter
- Scroll wheel which lights up blue

Delivery volume

- 1 laser mouse
- 1 USB / PS/2-adapter
- 1 KeyM@n CD with driver software
- 1 printed manual

Approvals

- CE, FCC, cURus, GOST-R, C-TICK, WHQL

System requirements

- USB or PS/2 interface
- CD or DVD drive

Technical data

- Number of buttons:
7 buttons
- Weight:
approx. 153 g (without packaging)
approx. 470 g (with packaging)
- Dimensions in mm:
approx. 131 x 80 x 46 (mouse)
approx. 250 x 250 x 90 (packaging)
- Storage temperature:
-20 °C to 65 °C
- Operating temperature:
0 °C to 40 °C
- Cable length:
approx. 1.80 m
- Resolution:
800 dpi (laser)
- Interface:
USB (PS/2 with adapter)
- Current consumption:
typ. 20 mA
- Packaging unit:
10 mice per master carton
12 master cartons per pallet

Order description

| <i>Order number</i> | <i>Housing colour</i> | <i>EAN-Code</i> |
|---------------------|-----------------------|-----------------|
| M-100R | silver / black | 4025112059629 |

Cherry Electrical Products Ltd
Unit L, Airport Executive Park
President Way, Luton, Beds
LU2 9NY

Phone: +44 (0) 1582 506140
Fax: +44 (0) 1582 506176
Internet: www.cherryuk.co.uk

The manufacturer accepts no liability for errors or non-availability, and reserves the right to change specifications without prior notice.

Technical data relates to product specifications only.
Features may differ from those described. Only drawings combined with product specifications shall be deemed binding.